

FIG. 2

_1





FIG. 4


					_		_													_				
	Help		Diagram Messages Proposed	A final validation is required to complete this configuration	MUST READ. There are 7038-6M2s not currently racked. It is rec	402 A The standalone p650 needs specific PDUs	(1) 3038 6M3: Dark Societ 1 has socialisment for 6765 E61 AIX VS	Rack Server 1 requires a display or ASCII terminal for initial setup	(i) A UPS is recommended with the server to provide protection from															
	<u>Si</u>			ব		- 47							-	,					N		<u>~</u> 0		2	
	Portfolio			7														8208			s)(Initia RS/600		: Rac	
	Profiles		.pSeries and RS/6000 2. Software 3. P⊡														Hardware Management Console	Series Control Workstation for 9078			Global Settings (United States)(Initial) Price File: US;Dollars;pSeries or RS/600	SUS	7038-6M2 : Rack Server 1 Software Products (7038-6M2 : Rack)	
			2. Softw		8		ations					11-D10	11-D20				ement (ions Vorkstal			(United	optio le	ck Ser acts (70	II,
	Options	Je	0009/		Cluster Model 1600		Express Configurations	은 등	3 R	6	2 2 2	1/O Drawer-(7311-D10)	1/O Drawer-(7311-D20	සු ද	8 8	6	Hardware Manageme	ontrol V	_		Settings US:Doll	Software Global Options	☐ 7038-6M2 : Rack Server 1 ☐ Software Products (7038-	
	>	New Initial Order	and RS	ے	uster M	☐ Cluster Switch ☐ IntelliStation	press C	pSeries 610	Series 630	Series 640	pSeries 650 7038-6M2	10 Dra	VO Dra	pSeries 655 pSeries 660	Series 670	pSeries 690	Irdware			Wizard	Global Se File:	Softwar	7038-61 Softwar	
	Configuration	New G	Series	Description	ਹੈ। □	5 E	ă O	এ <u>ে</u> পু পু) () () ()	\@ \@	ე_ქ გ_ქ	P	F,	ე <u>_</u> გ გ		S.	里 Y	3.6	,	-	Pric			
		11. 1	<u></u>	Ö	[+ +		+	1		I	L		+ +	+		+	<u> </u>	√	ਰੰ				D
1	Jit View	ië.	→ SYS: 1 New							_														
		11 5	-																					- 1
	File Edit	-₩ Customer:	SYS																					

,



1

-1G.(



<u>G</u>

1	一	-												_	_			-	
Help	8	Diagram Messages Proposed	A final validation is required to complete this configuration	─────────────────────────────────────	7038-6M2: Rack Server 1, has requirement for 5765-E61 AIX V5.	Rack Server 1 requires a display or ASCII terminal for initial setup A UPS is recommended with the server to provide protection from	The total number of RIO-G cables is - on D10 IO Drawers: 2; Dou	GreenLight SuperSale] IBM is currently offering discount on P650	702	70/									
Portfolio			ব						Ţ	-						itial) 500		er SCK	
		3. P∆										sole	for 9078			ates)(Ini	_	/O Draw 6M2 : R	Н
Profiles		Software			Suo				() () () () () () () () () () () () () (ent Con	s rkstation			United Stansing	Options Server	-D10):1 s (7038-	
Options	<u></u>	1.pSeries and RS/6000 2. Software 3. PI□I		Cluster Model 1600 Cluster Switch IntelliStation	Express Configurations pSeries 610			. ~	10 Drawer-(7311-D10)	,		oSenes 690 Hardware Management Console	oSeries HA Solutions oSeries Control Workstation for 9078			Global Settings (United States)(Initial) Price File: US;Dollars;pSeries or RS/600	Software Global Options	10 Drawer-(7311-D10) : I/O Drawer Software Products (7038-6M2 : Rack)	
	New Initial Order	nd RS/6		Cluster Model Cluster Switch IntelliStation	Express Cor Series 610	Series 620 Series 630	pSeries 640	7038-6M2	O Draw	pSeries 655 pSeries 660	Series 670	Senes 690 Hardware M	eries HA		PIG FIG	Slobal Se File: U	Software	O Draw	
Configuration	New Ini	Series a	Description	335 D06	TA S		_ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			 \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Z \ <u>\</u> \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \	_ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	-	WE	ا اغز			
		4- g-	ĕ	H E	# #	田田	+ +)		+ +		I I	+ +	⊽	ð		[)	卤
View	je:	New					-												Δ
	-∯ Customer:	⊕ ⊗SYS: 1 New																	
iii Û ∏	Œ.	⊗ ⊞																	∇

		8/17	
		FIG. 8	_
Help	Diamam Maccanac Promocod	A final validation is required to complete this configuration	
t View Configuration Options Profiles Portfolio		Description □ Cluster Model 1600 □ Cluster Switch □ Discription □ Discriptio	
File Edit	Customer:	7	

SYS: 1 New Initial Order Tourish Foundary Coustomer 1 New Initial Order 1.0 Solitor 1.0 Solit
2 □ □ □ □ □ □ □ □ □
Commigration Options Fronties Fronties Fronties Fronties Commigration Options Fronties Commigration Com
3 □ □ □ ⊗
A □ □ ○ ○ ○ A □ ○ ○ ○ A □ ○ ○ ○ A □ ○ ○ ○ A □ ○ ○ ○ A □ ○ ○ ○ A □ ○ ○ ○ A □ ○ ○ ○ A □ ○ ○ ○ ○ A □ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○
⊗ □ □ ⊗ ∨ Institution of the property

1

G. 1(


S			31								_			24						
			4		MUST READ: There are 7038-6M2s not currently racked. It is rec	The standalone p650 needs specific PDUs SW applications not supported by ECFGRS6000 should be valida	7038-6M2: Rack Server 1, has requirement for 5765-E61 AIX V5.	A UPS is recommended with the server to provide protection from	ine total number of KIO-G caples is - on D to 10 Drawers: 2, bou The total number of SPCN cables in D10/D20 10 Drawer is: 2. Dr	P650										
				<u>.</u>	 	d be	61 Al	ection	ers: 2 er is:	F		1	واو	1						Į.
					a ç	shoul	165-E	b bot	Draw Draw	NZ X		1		ا اور	Nizar					
				S Pue	rently	9000	for 57	o vid	2 0	Mare	Text	1	킬통	Miz .	Ses					
		-	\parallel	a this	ੇ ਹੋ :	ous GRS	ment .	5 5	2 <u>5</u>	S	ssage		عَاِهَ	اچ د	<u>8</u>					
				Hole	12s nr	E E	quire	serve .	Sis-Cario	9 e	d Me				New New					
			1	8	№	spec ed by	as re	the :	ables ables	Jump to P650 Software Wizard	Detailed Message Text	Jump to wizard	Launch New 7311-D10 Wizard Launch New 7014-T00 Wizard	Launch New Tape Wizard	Launch New Services Wizard					
				E	. jo	reeds Ipport	7. T.		3 8			5 -	تاد	. تــــــــــــــــــــــــــــــــــــ	ا د					
			Messages Proposed	A final validation is required to complete this configuration	ere a	The standalone p650 needs specific PDUs 3W applications not supported by ECFGRS	Serve	ende Services	I ne total number of KIO-5 cables is - on D io 10 Drawers: 2, bou The total number of SPCN cables in D10/D20 IO Drawer is: 2. Dr	GreenLight SuperSale]										
			A] je je		one p	Rack		mber m	S B										
			ages		Α̈́.	andal oplica	3M2:	orive Sis re	章 章											
			Mess	le il	AUST	The st SW ap	0384		교 하 당 당											
			E	11	. - .)⊗<	_ 0,	<u>, </u>	z √, z⊝z∈	- - >>>	⊡ ∰										
	윤		Diagram							į į										
			F	<u> </u>									-			·				
	등	- 11	1111											_						
	탕			ಠ						-1	7						(1) (1) (1) (1) (1)		Wer	§ _
	Portfolio			ಠ										<u>e</u>	r 9078		es)(Initial) r RS/600		Drawer 100kg	
			3 Pd											Sonsole	no for 9078		l States)(Initial) ries or RS/600	13 24): I/O Drawer	30-01VIZ . NACA
	Profiles Port		3 Pd				suo				-020)			nent Console	IS rketation for 9078		United States)(Initial) s;pSeries or RS/600	Options Second	-D10): I/O Drawer	IS (1000-01912. Nath)
	Profiles		3 Pd		1600		gurations			070	(7311-020)			lagement Console	olutions Workstation for 9078		ngs (United States)(Initial) Jollars;pSeries or RS/600	obal Options	(7311-D10) : I/O Drawer	Oddels (1030-01412 . Nach)
		ia	3 Pd		fodel 1600	ion Seesansi	Configurations 310	320 330	540	M2	awer-(7311-D20)		070	osu e Management Console	1A Solutions Control Workstation for 9078		Settings (United States)(Initial) US;Dollars;pSeries or RS/600	are Global Options	awer-(7311-D10) : I/O Drawer	Alle Floudicis (1000-01912 - Nach)
	Options Profiles		3 Pd		ster Model 1600	IIIStation	ress configurations ries 610	ries 620 ries 630	ries 640	038-6M2	O Drawer-(7311-D20)	rries 655 rries 660	ries 670	thes bed dware Management Console	ries HA Solutions	ard	Slobal Settings (United States)(Initial) File: US;Dollars;pSeries or RS/600	Software Global Options	0.00-01/1/2	SOLIWATE FLOUDCIS (1030-01912 - NACA)
	Options Profiles		3 Pd		Cluster Model 1600	Intellistation	Dexpress Comigurations Describes 610) pSeries 620) pSeries 630) pSeries 640	€ 7038-6M2	10 Drawer (7311-D20)	1 pSeries 655 D pSeries 660) pSeries 670	J psenes by J Pardware Management Console	Describes HA Solutions Oceanies Control Workstation for 9078	Wizard	Global Settings (United States)(Initial) Price File: US;Dollars;pSeries or RS/600		100 Drawer-(7311-D10) : I/O Drawer 1	Soliwate Floudicis (1030-01012 - Ndix)
	Options Profiles	1 New Initial Order	00 2 Software 3 P □		Cluster Model 1600			90	ōē	€ 7038-6M2	7 (50	ā	×		a) c	00 00 0	A SULWAIE FLOUDCIS (1030-01MZ - Nach)
	Configuration Options Profiles	ᄱ	1 DSeries and RS/6000 2 Software 3 P		Cluster Model 1600			90		£ 7038-6M2	7 (Deries 655	⊕ © pSeries 670	50	ā	Qty Wizard	Global Settings (United States)(Initial) Price File: US;Dollars;pSeries or RS/600		00 00 0	A Soliwate Floudicis (1000-014).
	View Configuration Options Profiles	9	1 DSeries and RS/6000 2 Software 3 P		Cluster Model 1600			90	ōē	⊕ 7038-6M2	7 (50	ā	×		a) c	00 00 0	
	idit View Configuration Options Profiles		1 DSeries and RS/6000 2 Software 3 P		Cluster Model 1600			90	ōē	⊕ 7038-6M2	7 (50	ā	×		a) c	00 00 0	Soliwale Frouncis (1939-9142 - Nath.)
	idit View Configuration Options Profiles	9	3 Pd		Cluster Model 1600			90	ōē	⊕ 7038-6M2	7 (50	ā	×		a) c	00 00 0	Soliwale Flourics (1030-01/12 - Nath.)


 L

G. 1,

	⊕ D Series HA Solutions ⊕ D Series Control Workstation for 9078 □ D Series Control Workstation for 9078	
Launch New Services Wizard		
Launch New 7311-D10 Wizard		
Jump to Wizard	E D pSeries 655	
Detailed Message Text	UO Drawer-(7311-D10) UD Drawer-(7311-D20)	
GreenLight SuperSale]	← 7038-6M2	
The total number of RIO-G cables is - on D10 IO Drawers: 2; Dou	# D pSeries 640	
A UPS is recommended with the server to provide protection from	□ Denies 620 □ Denies 630	
7038-6M2: Rack Server 1, has requirement for 5765-E61 AIX V5.		
The standalone p650 needs specific PDUs (1) SW anningstant supported by ECECESCON should be valided.	□ Cluster Switch □ IntelliStation	
 A final validation is required to complete this configuration MUST READ: There are 7038-6M2s not currently racked. It is rec 	Cluster Model 1600	
	nd RS/6000 2. Software 3. PI	± × × × × × × × × × × × × × × × × × × ×
\otimes	1 New Initial Order	A Customer:
The second secon		~ ->() (유)
Help	Configuration Options Profiles Portfolio	Edit View

13/17 E





ı




FIG. 15




		Diagram Messages Proposed	To Fit					,										
Configuration Options Profiles Portfolio Help	② □ □ ⊗ ✓ 1 New Initial Order		Description	☐ Displays (0 X-SELL Product) ☐ Networking (0 X-SELL Product)	 ☐ Cryptographic Coprocessor (0 X-SELL Product) ☐ Printer Hardware (0 X-SELL Product) 	☐ DPS (4 X-SELL Products) ☐ D UPS to Support Back Mount Servers	-LD 9910-M30 Pulsar Evolution 3000iRM, 3000VA, 200-240V, 50/60HZ	—(1) 9910-P33 PowerWare UPS 5125 3000VA,220-240V, 50/60 —(1) 9910-A30 APC Smart UPS 5000VA. 220-240V. 50/60HZ	C Current	Automated Tape Library	Ousk The Disk The Dis	— Optical	Strorage Area Network	Oto Misser	┪	L. Price File: US;Dollars;pSeries or RS/6000 Comm; 2003/04/10		
File Edit View		+ SYS: 1 New									-							

1